


Scinor® Pressurized Ultrafiltration Module Scinor® SMT600-P80



Product Features & Benefits

- The characters of ≥ 5 N of mechanical strength and double potting ensures a variety of extreme physical cleaning to result in high system recovery and low OPEX.
- Allowed extreme pH range (1-13) & 5,000 mg/l of chlorine ensures high restorability and long-operating life
- 0.1 μ m nominal pore size distributed in uniform and homogeneous fiber ensures high rejection on particles, bacteria, colloid & virus for protecting downstream.
- Innovation of permanent hydrophilic technology ensures outstanding characters of high permeability
- Outside-In configuration packed with advanced PVDF hollow capillary fiber ensures to accommodate to wider feed water quality
- Not only standard fitting enhance facility on installation, but no gap to replace to SFP-2880 is its benefit

Capillary Fiber Specifications

Category	Hollow Fiber/Outside-In
Made by Process	TIPS
Materials	PVDF
Nominal Pore Size	0.1 μ m
I.D/O.D	0.7 mm/1.3mm
Burst Pressure	1.6 MPa

Modules Specifications

Housing Materials	Housing Materials
Potting Materials	Potting Materials
Flow Configuration	Outside-In
Sealing Type	O-Ring/EPDM
A Port Size	Rp 3/8" Female Thread
B/C/D Port Size	DN50, Coupling
Packed area	80 m ²
Module Volume (Water)	55 Liter
Weight(With Water/Empty)	100/45 Kilogram
Packing Weight	72 Kilogram
Pressure tolerance	0.6 MPa

Scinor[®] Pressurized Ultrafiltration Module **Scinor[®] SMT600-P80**

Applications & Operating Parameters

Temperature	1~40℃
pH range during operating	1~11
Max. Chlorine Tolerance	5,000 mg/L
pH Range during CIP	1~13
Typical Flux	40~120 L/(m ² .hr)
Typical Tran-membrane Pressure	0.02~0.15 Mpa
Typical Backwash Flux	50~120 L/(m ² .h)
Typical Air Scour Capacity	5~12 Nm ³ /(h.module)
Max. Air Scour Feed Pressure	0.25 Mpa
Max. Feed Pressure	0.4 Mpa
Max. Trans-membrane Pressure	0.3 Mpa
Max. Backwash Pressure	0.25 Mpa
Typical Filtered Capacity	3.2 ~ 9.6 m ³ /(h.module)
Filtered Water Turbidity	≤ 0.1 NTU
Filtered Water SDI ₁₅	≤ 3.0
E.Coli Removal	No Detected per 100ml sampling
Total Bacterial Count	<3 (CFU/mL)

Important Information

- Proper Start-up is essential to maintain high performance for UF system and to prevent membrane damage. Before commissioning or restart after long-term shutdown, installation of the modules, Pretreatment, instrument calibration and other system checks should be processed and calibrated. Please refer to the product technical manual.
- Module to be freeze & exposed on sunshine shall cause irreversible damage, please refer to product technical manual or inform us to get proper measures for storage and transportation if in particular area or conditions.
- Assembly and operating of UF system should be strictly followed with product technical manual and this bulletin, Any break of limitation will cause the limited warranty (Doc No. BSF-WA03-REV0/04) will be null and void.
- When initiate start-up, operating capacity shall be increase up slowly in order to accommodate to the feed & prevent from any abrupt pressure. To target 50% of design capacity at beginning of 2-24 hours is recommended, especially on wastewater application.

Beijing Scinor Membrane Technology Co., Ltd

F8, Xueyuan International Tower,
1 Zhichun Road
Haidian District, Beijing, 100083,
P.R China

Tel: +86 (10) 6975 6503
Fax: +86 (10) 6975 6503
Mail: Info@scinormem.com
Website: www.scinormem.com

The information provided in this bulletin contains merely general descriptions to illustrate product characteristics or parameter. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use. Scinor assumes no obligation or liability for the information in this document if applied data come out deviations based on the mentioned above.

The information described above contained herein and seller's product are provided "AS IS" without warranty of any kind, either expressed or implied, including, but not limited to, the implied warranties of merchantability, fitness for any particular purpose or use, or non-infringement of intellectual property. In no event shall seller be liable for any special, incidental, indirect, or consequential damages of any kind, or any damages whatsoever resulting from the use of information contained herein and seller's product.